
SECTION 1 — MATERIAL IDENTIFICATION

PRODUCT NAME: StaticWorx Buff
Floor buffing solution

MANUFACTURED FOR: StaticWorx, Inc.
PO Box 590069
Newton, MA 02459
www.staticworx.com

TELEPHONE NUMBER: 617-923-2000

EMERGENCY TELEPHONE NUMBER: 800-255-3924 or Poison Center

SECTION 2 – HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS Number	PEL ppm	TWA ppm	STEL ppm	%
Not a hazardous mixture, as defined in 29 CFR 1910, 1200 and M.G.L. c. 111F					
Contains: Glycol Ethers*					<4

*LISTED CHEMICAL SUBJECT TO REPORTING REQUIREMENTS OF SEC.313 OF TITLE III.

SECTION 3 — PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 212

SPECIFIC GRAVITY (WATER=1): 1.02

VAPOR PRESSURE (mm Hg): 17

VAPOR DENSITY (AIR=1): 1.1

VISCOSITY (CPS): 10

pH 8.4 +/- 0.5

APPEARANCE AND ODOR: White milky emulsion

EVAPORATION RATE (Butyl Acetate = 1): 0.36

SOLUBILITY IN WATER: Complete

MELTING POINT: N/A

DECOMPOSITION TEMPERATURE: N/A

AUTO IGNITION TEMPERATURE: N/A

SECTION 4 – FIRE AND EXPLOSION DATA

FLASH POINT (°F):	None
LOWER FLAMMABLE LIMIT:	N/A
UPPER FLAMMABLE LIMIT:	N/A
EXTINGUISHING MEDIA:	N/A
FIRE-FIGHTING PROCEDURE:	N/A
FIRE AND EXPLOSION HAZARDS:	N/A

SECTION 5 – REACTIVITY DATA

CHEMICAL STABILITY:	Stable
CONDITIONS TO AVOID:	Freezing, extreme heat
INCOMPATIBILITY:	Acids, oxidizers
POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION OF BYPRODUCT:	Thermal decomposition may yield carbon monoxide

SECTION 6 – HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY:	No primary route of entry
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:	N/A
POTENTIAL HEALTH EFFECTS:	
ACUTE:	Causes eye and skin irritation
CHRONIC:	Redness of skin
CARCINOGENICITY:	No
SIGNS AND SYMPTOMS OF EXPOSURE:	Irritation, redness of skin, eyes.
N.T.P:	N/A
IARC Monographs:	N/A
OSHA Regulated:	N/A

SECTION 7 – FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:	Flush with water for 15 minutes. Contact a physician if irritation occurs.
SKIN CONTACT:	Wash with soap and water.
INGESTION:	Drink milk, water, fruit juice, induce vomiting - contact a physician.

SECTION 8 — PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:	Dispense sand, sawdust, or vermiculite. Collect and place in plastic waste container. Wash area thoroughly with water.
WASTE DISPOSAL METHOD:	Use sanitary landfill disposal, (not a hazardous waste) according to federal, state and local regulations. (RCRA; subtitle D)
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:	Do not mix with other chemicals, store away from heat. KEEP FROM FREEZING. Store above 40°F.
OTHER PRECAUTIONS:	KEEP OUT OF REACH OF CHILDREN.

SECTION 9 — EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:	Not normally required with good ventilation.
VENTILATION:	Assure fresh circulation
EYE/FACE PROTECTION:	Wear gloves and goggles if contact with material is likely.
SKIN PROTECTION:	Normal room ventilation – assure fresh air circulation.
WORK/HYGIENIC PRACTICES	Do not eat or drink next to material. Wash hands after working with material.

SECTION 10 – TRANSPORTATION 49 CFR

OSHA:	Not regulated
DOT:	Not regulated
UN:	Not regulated
LABELS:	No

SECTION 11 – OTHER INFORMATION

HMIS RATING:	Health: 1 Flammability: 0 Reactivity: 0 Personal Protective Equipment: B
HAZARD RATING SCALE:	0 = Minimal; 1 = Slight; 2 = Moderate, 3 = Serious; 4 = Severe

The product manufacturer believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Further more, vendee assumes the risk in use of the material.